

# UG BOSS PRO 125CC



20/24

- Electric Start
- ! Hazard Indicator
- Front Disk Brake
- Leg Guard
- Magnetic Keyock
- Fuel Gauge



Plot No. 84, Kira road.

P.O Box 24281, Kampala -Uganda

Call: +256 756 670 579 / 780 134 884

Email:sales@simbaautomotives.com

Website: www.simbaautomotives.com

|                   |  |                     |  |
|-------------------|--|---------------------|--|
| Motorcycle Model  | UG BOSS PRO 125cc  | Clutch type         | Manual Multi-clip  |
| Motorcycle Type   | Off-Road   | Brakes:             | Front; Disk Brake, Rear; Drum Brake  |
| Max Speed         | ≥90Km/h  | Frame Type          | Semi-Double cradle, High Tensile Steel   |
| Engine Type       | 4-Stroke, Single cylinder, air cooled  | Tyres               | Front tyre; 80/90-21 M/C 48P<br>Rear Tyre; 100/80-18 M/C 58P                   |
| Engine Model      | 157FMI   | Wheel Base          | 1340mm   |
| Displacement      | 124cc  | Ground Clearance    | 260mm  |
| Engine Power      | 9.2kw@7500rpm  | Overall Length      | 2090mm   |
| Maximum Torque    | 11.6 (N.m) at 6500 RPM   | Overall Width       | 830mm  |
| Start System      | Kick and Electric Start  | Overall Height      | 1115mm   |
| Transmission      | Constant Mesh 5-Speed  | Seat height         | 840mm  |
| Suspension        | Front; Heavy duty spring with telescopic fork,Rear; Heavy duty spring fork / swing arm | Standard Loading    | 160kg (Including Driver)   |
| Compression Ratio | 10.0:1   | Gear Ratio          | 1st Gear 2.909, 2nd gear 1.867, 3rd Gear 1.316, 4th Gear 1.000, 5th gear 0.833 |
| Bore Stroke       | 54.0mm x 54.0mm  | Lubrication         | Pressure Splash  |
| Ignition          | C.D.I  | Battery             | 12V 7Ah Dry  |
| Fuel System       | Carburetor, fuel tank, cock  | Engine Oil Capacity | 1.2 Liters   |
| Tank Capacity     | 12 Liters  | Weight              | 107Kg  |
| Instrumentation   | Fuel Gauge   | Protection          | Metallic Leg-guard   |

